

# HO-400 / HO-400R INDIRECT FIRED SPACE HEATER



## INFORMATION SHEET

### FEATURES

- Diesel, oil, or kerosene
- Heated fuel filter
- 110% steel secondary containment
- Fully welded 16 ga 304 stainless steel heat exchanger
- Body panels made of 16 ga carbon steel with chip-resistant powder coating
- Flat-free tires with reinforced hubs
- Optional 60 or 118 US gal (227 or 447 l) fuel tank
- Riello burner



### SPECIFICATIONS

	HO-400	HO-400R
<b>BTUH</b>	325,000 - 390,000 BTUH 95 - 114 kW	325,000 - 390,000 BTUH 95 - 114 kW
<b>Air Movement</b>	2,400 CFM 68 m <sup>3</sup> /min	3,500 CFM 99 m <sup>3</sup> /min
<b>Weight</b>	580 lbs 263 kg	600 lbs 272 kg
<b>Dimensions</b>	70" x 30" x 52" 178 x 76 x 132 cm	70" x 30" x 55" 178 x 76 x 140 cm
<b>Power Supply</b>	120 V / 15 A	120 V / 15 A
<b>Current Draw</b>	9 A	8 A
<b>Ducting Capability</b>	50' max 15 m max	100' max 30 m max
<b>Recirculating</b>	No	Up to 50' Up to 15 m
<b>Certification</b>	CSA / UL	CSA / UL
<b>Fuel Tank Capacity</b>	48 US gal 182 l	48 US gal 182 l
<b>Run Time</b>	16 hrs @ 3 gal / hr 16 hrs @ 11 l / hr	16 hrs @ 3 gal / hr 16 hrs @ 11 l / hr
<b>Fan Power</b>	3/4 hp 0.55 kW	1 hp 0.74 kW
<b>Thermostat</b>	Yes	Yes